

**बिड दस्तावेज़ / Bid Document**

बिड विवरण/Bid Details	
बिड बंद होने की तारीख/समय /Bid End Date/Time	09-03-2026 19:00:00
बिड खुलने की तारीख/समय /Bid Opening Date/Time	09-03-2026 19:30:00
बिड पेशकश वैधता (बंद होने की तारीख से)/Bid Offer Validity (From End Date)	30 (Days)
मंत्रालय/राज्य का नाम/Ministry/State Name	Bihar
विभाग का नाम/Department Name	Rural Development Department Bihar
संगठन का नाम/Organisation Name	Rural Development Department
कार्यालय का नाम/Office Name	Bdo Ara Sadar
कुल मात्रा/Total Quantity	9
वस्तु श्रेणी /Item Category	Surf Board - Outdoor Gym Equipment (Q3) , Chest Press - Outdoor Gym Equipments (Q3) , Twister - Outdoor Gym Equipment (Q3) , Leg Press - Outdoor Gym Equipments (Q3) , Parallel Bar - Outdoor Gym Equipment (Q3) , Sit Up Board - Outdoor Gym Equipment (Q3) , Shoulder Builder / Arm Wheel - Outdoor Gym Equipment (Q3) , Air Walker / Stroller - Outdoor Gym Equipment (Q3)
एमएसएमई के लिए अनुभव के वर्षों और टर्नओवर से छूट प्रदान की गई है/MSE Relaxation for Years of Experience and Turnover	No
स्टार्टअप के लिए अनुभव के वर्षों और टर्नओवर से छूट प्रदान की गई है /Startup Relaxation for Years of Experience and Turnover	No
विक्रेता से मांगे गए दस्तावेज़/Document required from seller	Experience Criteria,Bidder Turnover,Certificate (Requested in ATC),Additional Doc 1 (Requested in ATC) *In case any bidder is seeking exemption from Experience / Turnover Criteria, the supporting documents to prove his eligibility for exemption must be uploaded for evaluation by the buyer
क्या आप निविदाकारों द्वारा अपलोड किए गए दस्तावेज़ों को निविदा में भाग लेने वाले सभी निविदाकारों को दिखाना चाहते हैं? संदर्भ मेन् है/Do you want to show documents uploaded by bidders to all bidders participated in bid?	No
बिड लगाने की समय सीमा स्वतः नहीं बढ़ाने के लिए आवश्यक बिड की संख्या   / Minimum number of bids required to disable automatic bid extension	1

**बिड विवरण/Bid Details**

दिनों की संख्या, जिनके लिए बिड लगाने की समय-सीमा बढ़ाई जाएगी। / <b>Number of days for which Bid would be auto-extended</b>	3
ऑटो एक्सटेंशन अधिकतम कितनी बार किया जाना है। / <b>Number of Auto Extension count</b>	1
बिड से रिवर्स नीलामी सक्रिय किया/Bid to RA enabled	No
बिड का प्रकार/Type of Bid	Two Packet Bid
प्राथमिक उत्पाद श्रेणी/Primary product category	Surf Board - Outdoor Gym Equipment
तकनीकी मूल्यांकन के दौरान तकनीकी स्पष्टीकरण हेतु अनुमत समय /Time allowed for Technical Clarifications during technical evaluation	2 Days
निरीक्षण आवश्यक (सूचीबद्ध निरीक्षण प्राधिकरण /जेम के साथ पूर्व पंजीकृत एजेंसियों द्वारा)/Inspection Required (By Empanelled Inspection Authority / Agencies pre-registered with GeM)	No
मूल्यांकन पद्धति/Evaluation Method	Total value wise evaluation
मध्यस्थता खंड/Arbitration Clause	No
सुलह खंड/Mediation Clause	No

**ईएमडी विवरण/EMD Detail**

आवश्यकता/Required	No
-------------------	----

**ईपीबीजी विवरण /ePBG Detail**

आवश्यकता/Required	No
-------------------	----

बोली विभाजन लागू नहीं किया गया/ Bid splitting not applied.

**एमआईआई खरीद वरीयता/MII Purchase Preference**

एमआईआई खरीद वरीयता/MII Purchase Preference	No
--	----

**एमएसई खरीद वरीयता/MSE Purchase Preference**

एमएसई खरीद वरीयता/MSE Purchase Preference	Yes
सूक्ष्म और लघु उद्यम मूल उपकरण निर्माताओं को खरीद में प्राथमिकता, यदि उनका मूल्य L1+X% तक की सीमा में हो / Purchase Preference to MSE OEMs available upto price within L1+X%	15

सूक्ष्म और लघु उद्यम को खरीद में प्राथमिकता के लिए बिड की मात्रा का अधिकतम प्रतिशत / Maximum Percentage of Bid quantity for MSE purchase preference	25
---	----

1. Purchase preference to Micro and Small Enterprises (MSEs) from the State of Bid Inviting Authority : Purchase preference will be given to MSEs as Micro and Small Enterprises from the State of Bid inviting Authority. If the bidder wants to avail the Purchase preference, the bidder must be the manufacturer of the offered product in case of bid for supply of goods. Traders are excluded from the purview of Public Procurement Policy for Micro and Small Enterprises. In respect of bid for Services, the bidder must be the Service provider of the offered Service. Relevant documentary evidence in this regard shall be uploaded along with the bid in respect of the offered product or service. If L-1 is not an MSE and MSE Seller (s) has/have quoted price within L-1+ 15% of margin of purchase preference /price band defined in relevant policy, such Seller shall be given opportunity to match L-1 price and contract will be awarded for percentage of 25 % of total quantity as defined/ decided in relevant policy.

2. Estimated Bid Value indicated above is being declared solely for the purpose of guidance on EMD amount and for determining the Eligibility Criteria related to Turn Over, Past Performance and Project / Past Experience etc. This has no relevance or bearing on the price to be quoted by the bidders and is also not going to have any impact on bid participation. Also this is not going to be used as a criteria in determining reasonableness of quoted prices which would be determined by the buyer based on its own assessment of reasonableness and based on competitive prices received in Bid / RA process.

### Surf Board - Outdoor Gym Equipment ( 1 pieces )

#### तकनीकी विशिष्टियाँ /Technical Specifications

[\\* जेम कटेगरी विशिष्टि के अनुसार / As per GeM Category Specification](#)

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	Type	Single, Double
CAPACITY	Maximum User Weight ( Kg )	100, 110, 120 (kilogram)
MATERIAL	Governing Specification for GI Pipes	BIS specification No IS 1239 ( Part 1 )- 2004, latest, BIS specification No IS 1161:2014, latest
	All the GI Pipes are ISI marked	Yes, No
	Main Central Pipe	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	Main Frame Pipe, Class as per IS 1239	Medium, Heavy, Not applicable for pipe as per IS 1161

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	<b>Main Central Pipe ( As per Clause 3, of IS 1161 ) Nominal Bore &amp; Wall Thickness</b>	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10 mm Thickness, Not Applicable
	<b>Grade Material as per table 2 of IS 1161</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>Movement (Paddle) Frame</b>	32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe, 50mm Nominal Bore G.I. Pipe
	<b>Movement ( Paddle ) Frame Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Movement ( Paddle ) Frame Pipe ( As per as per Clause 3, of IS 1161 ) , Nominal Bore &amp; Wall Thickness</b>	32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, Not Applicable
	<b>Grade Material as per table 2 IS 1161</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>Connecting Links</b>	25 mm Nominal Bore G.I. Pipe, 32 mm Nominal Bore G.I. Pipe, 40 mm Nominal Bore G.I. Pipe, 10 mm thick MS plates, 12 mm thick MS plates
	<b>Connecting Links Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for M.S. Plates and Pipes as per IS 1161
	<b>Connecting Link Pipe ( As per Clause 3, of IS 1161 ) Nominal Wall &amp; Thickness</b>	25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, 32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, Not Applicable
	<b>Grade Material (as per table 2 of IS 1161 )</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>Handle Frame</b>	25mm Nominal bore G.I. pipe, 32mm Nominal bore G.I. pipe

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	<b>Handle Frame Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Handle Frame Pipe ( as per IS 1161 ) as per clause 3, Nominal Wall &amp; Thickness</b>	25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, 32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, Not Applicable
	<b>Grade Material per table 2 of IS 1161</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>Foundation Pipes with anchoring</b>	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	<b>Nominal Bore of Foundation Pipe</b>	80mm, 100mm, 125mm, 150mm
	<b>Foundation Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Foundation Pipe Pipe ( as per IS 1161 ) as per clause 3, Nominal Wall &amp; Thickness</b>	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, Not Applicable
	<b>Grade Material (as per table 2 of IS 1161)</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>M S Foundation Plate Thickness</b>	10, 12 (millimeter)
	<b>Bearings</b>	Ball Bearing, Tapered Roller Bearing
	<b>Foot Rest</b>	Fibre Reinforced Plastic, Aluminum casting material, C.I., LDPE, HDPE, Nylon
OTHER REQUIREMENTS	<b>Installation</b>	Included, Not Included
CERTIFICATION	<b>Certification ( Safety and Quality Requirements )</b>	As per European Standard EN 16630, No
WARRANTY	<b>Warranty ( years )</b>	2, 3, 4, 5 (year)

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Mohammad Nishar Siddique	802301,GRAM PANCHAYAT, BHAGHIPAKAD	1	15

**Chest Press - Outdoor Gym Equipments ( 1 pieces )**

तकनीकी विशिष्टियाँ /Technical Specifications

\* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	Type	Chest Press Single, Chest Press Double
CAPACITY	Maximum User Weight ( Kg )	100, 110, 120 (kilogram)
MATERIAL	<b>Governing Specification for GI Pipes</b>	BIS specification No IS 1239 ( Part 1 )- 2004, latest, BIS specification No IS 1161:2014, latest
	<b>All the GI Pipes are ISI marked</b>	Yes, No
	<b>Main Central Pipe</b>	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	<b>Main Central Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Handle Frame</b>	32mm Nominal bore G.I. pipe, 40mm Nominal bore G.I. pipe
	<b>Handle Frame Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Seat Frame</b>	32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe
	<b>Seat Frame Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Connecting Links</b>	25mm Nominal Bore G.I. Pipe, 32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe, 10mm thick MS plates, 12mm thick MS plates
	<b>Connecting Links Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for M.S. Plates and Pipes as per IS 1161
	<b>Foot Rest Pipe</b>	25mm Nominal Bore G.I. Pipe, 32mm Nominal Bore G.I. Pipe
	<b>Foot Rest Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	<b>MS Foundation Plate Thickness</b>	10, 12 (millimeter)
	<b>Foundation Pipes with anchoring</b>	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	<b>Nominal Bore of Foundation Pipe</b>	80mm, 100mm, 125mm, 150mm
	<b>Foundation Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Seat and Back Rest</b>	2mm Thick G.I. Seat with uniform bending radius to avoid sharp edges, 3mm thick, HDPE with uniform bending radius to avoid sharp edges, 6mm thick, Fibre Reinforced plastic with uniform bending radius to avoid sharp edges, 2.5mm thick, M.S. Perforated with uniform bending radius to avoid sharp edges, 3mm thick, LLDPE with uniform bending radius to avoid sharp edges
	<b>Bearings</b>	Ball Bearing, Tapered Roller Bearing
OTHER REQUIREMENTS	<b>Installation</b>	Included, Not Included
CERTIFICATION	<b>Certification ( Safety and Quality Requirements )</b>	As per European Standard EN 16630, No
WARRANTY	<b>Warranty ( years )</b>	2, 3, 4, 5 (year)

**परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity**

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Mohammad Nishar Siddique	802301,GRAM PANCHAYAT, BHAGHIPAKAD	1	15

**Twister - Outdoor Gym Equipment ( 1 pieces )**

**तकनीकी विशिष्टियाँ /Technical Specifications**

[\\* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification](#)

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
---------------------	-------------------------------------	---

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	<b>Type</b>	Double Twister ( Both Standing ), Double Twister ( Both Sitting ), Double Twister ( One standing and one sitting ), Triple Twister ( Three standing ), Triple Twister ( Three Sitting ), Tripple Twister ( Two standing, one sitting ), Tripple Twister ( one standing, two sitting ), Single Twister Standing, Single Twister Sitting
CAPACITY	<b>Maximum User Weight ( Kg )</b>	100, 110, 120 ( <b>kilogram</b> )
MATERIAL	<b>Governing Specification for GI Pipes</b>	BIS specification No IS 1239 ( Part 1 )- 2004, latest, BIS specification No IS 1161:2014, latest
	<b>All the GI Pipes are ISI marked</b>	Yes, No
	<b>Main Central Pipe</b>	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	<b>Main Frame Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Main Central Pipe ( As per Clause 3, of IS 1161 ) Nominal Bore &amp; Wall Thickness</b>	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10 mm Thickness, Not Applicable
	<b>Grade Material as per table 2 of IS 1161</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>Standing/ Sitting Twister Frame Pipe</b>	25 mm Nominal Bore G.I. Pipe, 32 mm Nominal Bore G.I. Pipe, 40 mm Nominal Bore G.I. Pipe, 50 mm Nominal Bore G.I. Pipe
	<b>Standing/ Sitting Twister Frame Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	<b>Standing/ Sitting Twister Frame Pipe (As per Clause 3, of IS 1161 ) Nominal Bore &amp; Wall Thickness</b>	32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, 25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, Not Applicable
	<b>Grade Material as per table 2 IS 1161</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>Rotating Disk Support Pipe at Bottom Pipe</b>	80 mm Nominal Bore G.I. Pipe, 100 mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150 mm Nominal Bore G.I. Pipe
	<b>Rotating Disk Support Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for M.S. Plates and Pipes as per IS 1161
	<b>Rotating Disk Support Pipe ( as per IS 1161 ) as per Clause 3, Nominal Bore &amp; Wall Thickness</b>	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10mm Thickness, Not Applicable
	<b>Grade Material (as per table 2 of IS 1161 )</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>Handle Frame Pipe</b>	25mm Nominal bore G.I. pipe, 32mm Nominal bore G.I. pipe, 40 mm Nominal bore G.I. pipe
	<b>Handle Frame Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Handle Frame Pipe ( as per IS 1161 ) as per clause 3, Nominal Wall &amp; Thickness</b>	25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, 32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, Not Applicable
	<b>Grade Material per table 2 of IS 1161</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	<b>Foundation Pipes with anchoring</b>	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	<b>Nominal Bore of Foundation Pipe</b>	80mm, 100mm, 125mm, 150mm
	<b>Foundation Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Foundation Pipe Pipe ( as per IS 1161 ) as per clause 3, Nominal Wall &amp; Thickness</b>	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10 mm Thickness, Not Applicable
	<b>Grade Material (as per table 2 of IS 1161)</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>M S Foundation Plate Thickness</b>	10, 12 (millimeter)
	<b>Bearings</b>	Ball Bearing, Tapered Roller Bearing
	<b>Foot Rest</b>	Fibre Reinforced Plastic, Aluminum casting material, C.I., LDPE, HDPE, Nylon
OTHER REQUIREMENTS	<b>Installation</b>	Included, Not Included
CERTIFICATION	<b>Certfication ( Safety and Quality Requirements )</b>	As per European Standard EN 16630, No
WARRANTY	<b>Warranty ( years )</b>	2, 3, 4, 5 (year)

परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Mohammad Nishar Siddique	802301,GRAM PANCHAYAT, BHAGHIPAKAD	1	15

### Leg Press - Outdoor Gym Equipments ( 1 pieces )

#### तकनीकी विशिष्टियाँ /Technical Specifications

\* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	Type	Leg Press Single, Leg Press Double
CAPACITY	Maximum User Weight ( Kg )	100, 110, 120 (kilogram)
MATERIAL	<b>Governing Specification for GI Pipes</b>	BIS specification No IS 1239 ( Part 1 )- 2004, latest, BIS specification No IS 1161:2014, latest
	<b>All the GI Pipes are ISI marked</b>	Yes, No
	<b>Main Central Pipe</b>	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	<b>Main Central Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Moving Frame Pipe</b>	32mm Nominal bore G.I. pipe, 40mm Nominal bore G.I. pipe
	<b>Moving Frame Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Foot Rest Frame/ Foot Rest Hinging Pipe</b>	25mm Nominal Bore G.I. Pipe, 32mm Nominal Bore G.I. Pipe
	<b>Foot Rest Frame Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for M.S. Plates
	<b>Connecting Links</b>	25mm Nominal Bore G.I. Pipe, 32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe, 10mm thick MS plates, 12mm thick MS plates
	<b>Connecting Links Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for M.S. Plates and Pipes as per IS 1161
	<b>MS Foundation Plate Thickness</b>	10, 12 (millimeter)
	<b>Foundation Pipes with anchoring</b>	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	<b>Nominal Bore of Foundation Pipe</b>	80mm, 100mm, 125mm, 150mm

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	<b>Foundation Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Bearings</b>	Ball Bearing, Tapered Roller Bearing
	<b>Seat and Back Rest</b>	2mm Thick G.I. Seat with uniform bending radius to avoid sharp edges, 3mm thick, HDPE with uniform bending radius to avoid sharp edges, 6mm thick, Fibre Reinforced plastic with uniform bending radius to avoid sharp edges, 2.5mm thick, M.S. Perforated with uniform bending radius to avoid sharp edges, 3mm thick, LLDPE with uniform bending radius to avoid sharp edges
OTHER REQUIREMENTS	<b>Installation</b>	Included, Not Included
CERTIFICATION	<b>Certification ( Safety and Quality Requirements )</b>	As per European Standard EN 16630, No
WARRANTY	<b>Warranty ( years )</b>	2, 3, 4, 5 (year)

**परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity**

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Mohammad Nishar Siddique	802301,GRAM PANCHAYAT, BHAGHIPAKAD	1	15

**Parallel Bar - Outdoor Gym Equipment ( 1 pieces )**

**तकनीकी विशिष्टियाँ /Technical Specifications**

\* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
Material	<b>Governing Specification for GI Pipes</b>	BIS specification No IS 1239 ( Part 1 )- 2004, latest, BIS specification No IS 1161:2014, latest
	<b>All the GI Pipes are ISI marked</b>	Yes, No
	<b>Vertical / Standing Pipes</b>	32 mm Nominal Bore G.I. Pipe, 40 mm Nominal Bore G.I. Pipe, 50 mm Nominal Bore G.I. Pipe, 80 mm Nominal Bore G.I. Pipe, 100 mm Nominal Bore G.I. Pipe, 25mm Nominal Bore G.I. Pipe
	<b>Vertical/ Standing Pipes, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	<b>Vertical / Standing Pipe (as per Clause 3 of IS 1161) , Nominal Bore &amp; Wall Thickness</b>	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, Not applicable
	<b>Horizontal Pipe</b>	25 mm Nominal Bore G.I. Pipe, 32 mm Nominal Bore G.I. Pipe, 40 mm Nominal Bore G.I. Pipe, 50 mm Nominal Bore G.I. Pipe
	<b>Horizontal Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Horizontal Pipe ( As per Clause 3, of IS 1161 ) Nominal Bore &amp; Wall Thickness</b>	32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, 25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, Not applicable
	<b>Grade Material as per table 2 of IS 1161</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>Foundation Pipes with anchoring</b>	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 3 mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 3 mm
	<b>Nominal Bore of Foundation Pipe</b>	32 mm, 40 mm, 50 mm, 80 mm, 100 mm, 38 mm
	<b>Foundation Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Foundation Pipe Pipe ( as per IS 1161 ) as per clause 3, Nominal Wall &amp; Thickness</b>	32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, 80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, Not Applicable
	<b>M S Foundation Plate Thickness</b>	10, 12 (millimeter)

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	<b>Bearings</b>	Ball Bearing, Tapered Roller Bearing, N.A.
	<b>Foot Rest</b>	Fibre Reinforced Plastic, Aluminum casting material, C.I., LDPE, HDPE, Nylon
Other Requirements	<b>Installation</b>	Included, Not Included
Certification	<b>Certification ( Safety and Quality Requirements )</b>	As per European Standard EN 16630, No
Warranty	<b>Warranty ( years )</b>	2, 3, 4, 5 (year)

**परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity**

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Mohammad Nishar Siddique	802301,GRAM PANCHAYAT, BHAGHIPAKAD	1	15

**Sit Up Board - Outdoor Gym Equipment ( 1 pieces )**

**तकनीकी विशिष्टियाँ /Technical Specifications**

\* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	<b>Type</b>	Single Station, Double Station
MATERIAL	<b>Type of Back Rest</b>	Perforated Sheet, Set of Rectangular Flat Pipes, Plain Sheet
	<b>Material of Back Rest</b>	Fibre Reinforced Plastic, Mild Steel Plate, LDPE, HDPE, Galvanized Iron(GI)
	<b>Governing Specification for GI Pipes</b>	BIS specification No IS 1239 ( Part 1 )- 2004, latest, BIS specification No IS 1161:2014, latest
	<b>All the GI Pipes are ISI marked</b>	Yes, No
	<b>Main Frame/Central Pipe</b>	50mm Nominal Bore G.I. Pipe, 80mm Nominal Bore G.I. Pipe, 100 mm Nominal Bore G.I. Pipe, 125mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	<b>Main Frame/Central Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	<b>Main Frame/Central Pipe ( As per Clause 3, of IS 1161 ) Nominal Bore &amp; Wall Thickness</b>	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10 mm Thickness, 50 mm NB with 2.9mm Thickness, 50 mm NB with 3.6mm Thickness, 50 mm NB with 4.5 mm Thickness, Not Applicable
	<b>Grade of Material as per table 2 of IS 1161</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>Foot Rest Pipe</b>	32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe, 50mm Nominal Bore G.I. Pipe
	<b>Foot Rest Pipe , Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Foot Rest Pipe ( As per as per Clause 3, of IS 1161 ) , Nominal Bore &amp; Wall Thickness</b>	32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, Not Applicable
	<b>Grade of Material as per table 2 IS 1161</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>Back Rest Frame Pipe and Connecting Links</b>	25 mm Nominal Bore G.I. Pipe, 32 mm Nominal Bore G.I. Pipe, 40 mm Nominal Bore G.I. Pipe
	<b>Back Rest Frame Pipe and Connecting Links, Class as per IS 1239</b>	Medium, Heavy, Not applicable for M.S. Plates and Pipes as per IS 1161
	<b>Back Rest Frame Pipe and Connecting Links ( As per Clause 3, of IS 1161 ) Nominal Wall &amp; Thickness</b>	25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, 32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, Not Applicable
	<b>Grade of Material (as per table 2 of IS 1161 )</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>Leg Support Pipe</b>	32mm Nominal bore G.I. pipe, 40 mm Nominal bore G.I. pipe, 50mm Nominal bore G.I. pipe

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	<b>Leg Support Pipe , Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Leg Support Pipe ( as per IS 1161 ) as per clause 3, Nominal Wall &amp; Thickness</b>	32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6mm Thickness, 50 mm NB with 4.5mm Thickness, Not Applicable
	<b>Grade of Material per table 2 of IS 1161</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>Foundation Pipes with anchoring</b>	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	<b>Nominal Bore of Foundation Pipe</b>	80mm, 100mm, 125mm, 150mm
	<b>Foundation Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Foundation Pipe Pipe ( as per IS 1161 ) as per clause 3, Nominal Wall &amp; Thickness</b>	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 125 mm NB with 4.5 mm Thickness, 125mm NB with 4.8 mm Thickness, 125 mm NB with 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 4.5 mm Thickness, 150 mm NB,165.1 mm OD & 4.8 mm Thickness, 150 mm NB,165.1 mm OD & 5.4 mm Thickness, 150 mm NB,165.1 mm OD & 5.9 mm Thickness, 150 mm NB,165.1 mm OD & 6.3 mm Thickness, 150 mm NB,165.1 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 4.5 mm Thickness, 150 mm NB,168.3 mm OD & 4.8 mm Thickness, 150 mm NB,168.3 mm OD & 5.4 mm Thickness, 150 mm NB,168.3 mm OD & 6.3 mm Thickness, 150 mm NB,168.3 mm OD & 8 mm Thickness, 150 mm NB,168.3 mm OD & 10 mm Thickness, Not Applicable
	<b>Grade of Material (as per table 2 of IS 1161)</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>M S Foundation Plate Thickness</b>	10, 12 (millimeter)
OTHER REQUIREMENTS	<b>Installation</b>	Included, Not Included
CERTIFICATION	<b>Certification ( Safety and Quality Requirements )</b>	As per European Standard EN 16630, No
WARRANTY	<b>Warranty ( years )</b>	2, 3, 4, 5 (year)

परिषदी/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity

क्र.सं./S.No.	परिषदी/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Mohammad Nishar Siddique	802301,GRAM PANCHAYAT, BHAGHIPAKAD	1	15

**Shoulder Builder / Arm Wheel - Outdoor Gym Equipment ( 1 pieces )**

तकनीकी विशिष्टियाँ /Technical Specifications

\* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	Type	Two Wheel, Three Wheel
MATERIAL	<b>Governing Specification for GI Pipes</b>	BIS specification No IS 1239 ( Part 1 )- 2004, latest, BIS specification No IS 1161:2014, latest
	<b>All the GI Pipes are ISI marked</b>	Yes, No
	<b>Main Central Pipe construction</b>	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	<b>Main Central Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Ring ( Wheel )</b>	25mm Nominal Bore G.I. Pipe, 32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe
	<b>Ring ( Wheel ) Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Pipe of Spokes of Wheel</b>	15mm Nominal bore G.I. pipe, 20mm Nominal bore G.I. pipe
	<b>Pipe of Spoke of Wheel , Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Connector Pipe ( between Main Central Pipe and Wheel )</b>	32 mm Nominal bore G.I. pipe, 40 mm Nominal bore G.I. pipe, 50 mm Nominal bore G.I. pipe
	<b>Connector Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>MS Foundation Plate Thickness</b>	10, 12 (millimeter)
	<b>Foundation Pipes with anchoring</b>	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	<b>Nominal Bore of Foundation Pipe</b>	80mm, 100mm, 125mm, 150mm

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	<b>Foundation Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Bearings</b>	Ball Bearing, Tapered Roller Bearing
OTHER REQUIREMENTS	<b>Installation</b>	Included, Not Included
CERTIFICATION	<b>Certification ( Safety and Quality Requirements )</b>	As per European Standard EN 16630, No
WARRANTY	<b>Warranty ( years )</b>	2, 3, 4, 5 (year)

**परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity**

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Mohammad Nishar Siddique	802301,GRAM PANCHAYAT, BHAGHIPAKAD	1	15

**Air Walker / Stroller - Outdoor Gym Equipment ( 1 pieces )**

**तकनीकी विशिष्टियाँ /Technical Specifications**

\* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
TYPE	<b>Type</b>	Single, Double
CAPACITY	<b>Maximum User Weight ( Kg )</b>	100, 110, 120 (kilogram)
MATERIAL	<b>Governing Specification for GI Pipes</b>	BIS specification No IS 1239 ( Part 1 )- 2004, latest, BIS specification No IS 1161:2014, latest
	<b>All the GI Pipes are ISI marked</b>	Yes, No
	<b>Main Frame</b>	80mm Nominal Bore G.I. Pipe, 100mm Nominal Bore G.I. Pipe, 125 mm Nominal Bore G.I. Pipe, 150mm Nominal Bore G.I. Pipe
	<b>Main Frame Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>leg movement frame</b>	32mm Nominal Bore G.I. Pipe, 40mm Nominal Bore G.I. Pipe, 50mm Nominal Bore G.I. Pipe

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	<b>Leg Movement Frame Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Handle Frame</b>	25mm Nominal bore G.I. pipe, 32mm Nominal bore G.I. pipe
	<b>Handle Frame Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Bearings</b>	Ball Bearing, Tapered Roller Bearing
	<b>Foot Rest</b>	Fibre Reinforced Plastic, Aluminum casting material, C.I., LDPE, HDPE, Nylon
	<b>MS Foundation Plate Thickness</b>	10, 12 (millimeter)
	<b>Foundation Pipes with anchoring</b>	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm
	<b>Nominal Bore of Foundation Pipe</b>	80mm, 100mm, 125mm, 150mm
	<b>Foundation Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
OTHER REQUIREMENTS	<b>Installation</b>	Included, Not Included
CERTIFICATION	<b>Certification ( Safety and Quality Requirements )</b>	As per European Standard EN 16630, No
WARRANTY	<b>Warranty ( years )</b>	2, 3, 4, 5 (year)

**परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity**

क्र.सं./S.No.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Mohammad Nishar Siddique	802301,GRAM PANCHAYAT, BHAGHIPAKAD	1	15

**Parallel Bar - Outdoor Gym Equipment ( 1 pieces )**

**तकनीकी विशिष्टियाँ /Technical Specifications**

[\\* जेम केटेगरी विशिष्टि के अनुसार / As per GeM Category Specification](#)

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
Material	<b>Governing Specification for GI Pipes</b>	BIS specification No IS 1239 ( Part 1 )- 2004, latest, BIS specification No IS 1161:2014, latest
	<b>All the GI Pipes are ISI marked</b>	Yes, No
	<b>Vertical / Standing Pipes</b>	32 mm Nominal Bore G.I. Pipe, 40 mm Nominal Bore G.I. Pipe, 50 mm Nominal Bore G.I. Pipe, 80 mm Nominal Bore G.I. Pipe, 100 mm Nominal Bore G.I. Pipe, 25mm Nominal Bore G.I. Pipe
	<b>Vertical/ Standing Pipes, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Vertical / Standing Pipe (as per Clause 3 of IS 1161) , Nominal Bore &amp; Wall Thickness</b>	80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, 32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, Not applicable
	<b>Horizontal Pipe</b>	25 mm Nominal Bore G.I. Pipe, 32 mm Nominal Bore G.I. Pipe, 40 mm Nominal Bore G.I. Pipe, 50 mm Nominal Bore G.I. Pipe
	<b>Horizontal Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161
	<b>Horizontal Pipe ( As per Clause 3, of IS 1161 ) Nominal Bore &amp; Wall Thickness</b>	32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, 25 mm NB with 2.6 mm Thickness, 25 mm NB with 3.2 mm Thickness, 25 mm NB with 4 mm Thickness, Not applicable
	<b>Grade Material as per table 2 of IS 1161</b>	YSt 210, YSt 240, YSt 310, YSt 355, Not Applicable
	<b>Foundation Pipes with anchoring</b>	750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm, 750mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 3 mm, 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 3 mm
	<b>Nominal Bore of Foundation Pipe</b>	32 mm, 40 mm, 50 mm, 80 mm, 100 mm, 38 mm
<b>Foundation Pipe, Class as per IS 1239</b>	Medium, Heavy, Not applicable for pipe as per IS 1161	

विवरण/Specification	विशिष्टि का नाम /Specification Name	बिड के लिए आवश्यक अनुमत मूल्य /Bid Requirement (Allowed Values)
	<b>Foundation Pipe Pipe ( as per IS 1161 ) as per clause 3, Nominal Wall &amp; Thickness</b>	32 mm NB with 2.6 mm Thickness, 32 mm NB with 3.2 mm Thickness, 32 mm NB with 4 mm Thickness, 40 mm NB with 2.9 mm Thickness, 40 mm NB with 3.2 mm Thickness, 40 mm NB with 4 mm Thickness, 50 mm NB with 2.9 mm Thickness, 50 mm NB with 3.6 mm Thickness, 50 mm NB with 4.5 mm Thickness, 80 mm NB with 3.2 mm Thickness, 80 mm NB with 4 mm Thickness, 80 mm NB with 4.8 mm Thickness, 100 mm NB with 3.6 mm Thickness, 100 mm NB with 4.5 mm Thickness, 100 mm NB with 5.4 mm Thickness, Not Applicable
	<b>M S Foundation Plate Thickness</b>	10, 12 (millimeter)
	<b>Bearings</b>	Ball Bearing, Tapered Roller Bearing, N.A.
	<b>Foot Rest</b>	Fibre Reinforced Plastic, Aluminum casting material, C.I., LDPE, HDPE, Nylon
Other Requirements	<b>Installation</b>	Included, Not Included
Certification	<b>Certification ( Safety and Quality Requirements )</b>	As per European Standard EN 16630, No
Warranty	<b>Warranty ( years )</b>	2, 3, 4, 5 (year)

**परेषिती/रिपोर्टिंग अधिकारी तथा मात्रा/Consignees/Reporting Officer and Quantity**

क्र.सं./S.N o.	परेषिती/रिपोर्टिंग अधिकारी /Consignee Reporting/Officer	पता/Address	मात्रा /Quantity	डिलीवरी के दिन/Delivery Days
1	Mohammad Nishar Siddique	802301,GRAM PANCHAYAT, BHAGHIPAKAD	1	15

**क्रेता द्वारा जोड़ी गई बिड की विशेष शर्तें/Buyer Added Bid Specific Terms and Conditions**

**1. Generic**

OPTION CLAUSE: The Purchaser reserves the right to increase or decrease the quantity to be ordered up to 25 percent of bid quantity at the time of placement of contract. The purchaser also reserves the right to increase the ordered quantity up to 25% of the contracted quantity during the currency of the contract at the contracted rates. The delivery period of quantity shall commence from the last date of original delivery order and in cases where option clause is exercised during the extended delivery period the additional time shall commence from the last date of extended delivery period. The additional delivery time shall be (Increased quantity ÷ Original quantity) × Original delivery period (in days), subject to minimum of 30 days. If the original delivery period is less than 30 days, the additional time equals the original delivery period. The Purchaser may extend this calculated delivery duration up to the original delivery period while exercising the option clause. Bidders must comply with these terms.

## 2. Buyer Added Bid Specific ATC

Buyer Added text based ATC clauses

Buyer Added text based ATC clauses

01. Bidder should have MSME/Udyam Registration Certificate
02. Bidder should have valid GST Registration Certificate
03. Bidder Should have valid PAN Card
04. Bidder or its authorized dealer should have IAF Approved Certification of ISO 9001: 2015, ISO 14001: 2015 & ISO 45001: 2018
05. Bidder should be Non- Blacklisted from any Central or State Organization, PSU, same will be required on INR 100/- Stamp Paper of Bihar State. only which will be not old beyond 4 months of date of bid opening
06. ITR Last three-year audited Report & balance sheet.
07. Average Annual Turnover Certificate issued by CA.
08. Bidder must have Submit Plague Integrity Certificate.
09. Bidder must have submit GST 3b Last 06 Month.
10. Bidder Must Have Submit Carector Certificate.
11. Bidder Must Have Submit Undertaking For Financial Standing.
12. Bidder Must Have Submit Declaration of Local Service Centre Availability.
13. Bidder Must Have Submit Escalation Matrix.

## अस्वीकरण/Disclaimer

The additional terms and conditions have been incorporated by the Buyer after approval of the Competent Authority in Buyer Organization, whereby Buyer organization is solely responsible for the impact of these clauses on the bidding process, its outcome, and consequences thereof including any eccentricity / restriction arising in the bidding process due to these ATCs and due to modification of technical specifications and / or terms and conditions governing the bid. If any clause(s) is / are incorporated by the Buyer regarding following, the bid and resultant contracts shall be treated as null and void and such bids may be cancelled by GeM at any stage of bidding process without any notice:-

1. Definition of Class I and Class II suppliers in the bid not in line with the extant Order / Office Memorandum issued by DPIIT in this regard.
2. Seeking EMD submission from bidder(s), including via Additional Terms & Conditions, in contravention to exemption provided to such sellers under GeM GTC.
3. Publishing Custom / BOQ bids for items for which regular GeM categories are available without any Category item bunched with it.
4. Creating BoQ bid for single item.
5. Mentioning specific Brand or Make or Model or Manufacturer or Dealer name.
6. Mandating submission of documents in physical form as a pre-requisite to qualify bidders.
7. Floating / creation of work contracts as Custom Bids in Services.
8. Seeking sample with bid or approval of samples during bid evaluation process. (However, in bids for [attached categories](#), trials are allowed as per approved procurement policy of the buyer nodal Ministries)
9. Mandating foreign / international certifications even in case of existence of Indian Standards without

specifying equivalent Indian Certification / standards.

10. Seeking experience from specific organization / department / institute only or from foreign / export experience.
11. Creating bid for items from irrelevant categories.
12. Incorporating any clause against the MSME policy and Preference to Make in India Policy.
13. Reference of conditions published on any external site or reference to external documents/clauses.
14. Asking for any Tender fee / Bid Participation fee / Auction fee in case of Bids / Forward Auction, as the case may be.
15. Buyer added ATC Clauses which are in contravention of clauses defined by buyer in system generated bid template as indicated above in the Bid Details section, EMD Detail, ePBG Detail and MII and MSE Purchase Preference sections of the bid, unless otherwise allowed by GeM GTC.
16. In a category based bid, adding additional items, through buyer added additional scope of work/ additional terms and conditions/or any other document. If buyer needs more items along with the main item, the same must be added through bunching category based items or by bunching custom catalogs or bunching a BoQ with the main category based item, the same must not be done through ATC or Scope of Work.

Further, if any seller has any objection/grievance against these additional clauses or otherwise on any aspect of this bid, they can raise their representation against the same by using the Representation window provided in the bid details field in Seller dashboard after logging in as a seller within 4 days of bid publication on GeM. Buyer is duty bound to reply to all such representations and would not be allowed to open bids if he fails to reply to such representations.

**All GeM Sellers/Service Providers shall ensure full compliance with all applicable labour laws, including the provisions, rules, schemes and guidelines under the four Labour Codes i.e. the Code on Wages, 2019; the Industrial Relations Code, 2020; the Occupational Safety, Health and Working Conditions Code, 2020; and the Code on Social Security, 2020 as and when notified and brought into force by the Government of India.**

**For all provisions of the Labour Codes that are pending operationalisation through rules, schemes or notifications, the corresponding provisions of the pre-existing labour enactments (such as The Minimum Wages Act, 1948, The Payment of Wages Act, 1936, The Payment of Bonus Act, 1965, The Equal Remuneration Act, 1976, The Payment of Gratuity Act, 1972, etc. and relevant State Rules) shall continue to remain applicable.**

**The Seller/ Service Providers shall, therefore, be responsible for ensuring compliance under:**

- **All notified and enforceable provisions of the new Labour Codes as mentioned hereinabove; and**
- **All operative provisions of the erstwhile Labour Laws until their complete substitution.**

**All obligations relating to wages, social security, safety, working conditions, industrial relations etc. and any other statutory requirements shall be strictly met by the Seller/ Service Provider. Any non-compliance shall constitute a breach of the contract and shall entitle the Buyer to take appropriate action in accordance with the contract and applicable law.**

[यह बिड सामान्य शर्तों के अंतर्गत भी शासित है /This Bid is also governed by the General Terms and Conditions](#)

जेम की सामान्य शर्तों के खंड 26 के संदर्भ में भारत के साथ भूमि सीमा साझा करने वाले देश के बिडर से खरीद पर प्रतिबंध के संबंध में भारत के साथ भूमि सीमा साझा करने वाले देश का कोई भी बिडर इस निविदा में बिड देने के लिए तभी पात्र होगा जब वह बिड देने वाला सक्षम प्राधिकारी के पास पंजीकृत हो। बिड में भाग लेते समय बिडर को इसका अनुपालन करना होगा और कोई भी गलत घोषणा किए जाने व इसका अनुपालन न करने पर अनुबंध को तत्काल समाप्त करने और कानून के अनुसार आगे की कानूनी कार्रवाई का आधार होगा।/In terms of GeM GTC clause 26 regarding Restrictions on procurement from a bidder of a country which shares a land border with India, any bidder from a country which shares a land border with India will be eligible to bid in this tender only if the bidder is registered with the Competent Authority. While participating in bid, Bidder has to undertake compliance of this and any false declaration and non-compliance of this would be a ground for immediate termination of the contract and further legal action in accordance with the laws.

---धन्यवाद/Thank You---